


TDS_613

HYDRO CURE

TECHNICAL DATA SHEET
akteonpaints.com



Hydro Cure_TDS_613_2025_v1.0_EN

Visit our website and learn
more about our products
akteonpaints.com

For further information:
contact@akteonpaints.com

Kifissias Ave. 44,
Amarousion
+30 210 440 2727

TECHNICAL DATA SHEET

HYDRO CURE

General purpose water based wood impregnant for preservation.

Main Features:

1. Water-based preservation impregnant for deep absorption into wood.
2. Prevents moisture absorption and reduces swelling, cracking, and deformation.
3. Protects against weathering, dirt, and surface degradation.
4. Stabilizes porous or aged wood surfaces.
5. Allows the wood to breathe—non-film-forming formula.
6. Low odor, low VOC, and easy cleanup with water.

Applications:

1. Natural stone: marble, granite, slate, sandstone, limestone.
2. Artificial stone, cultured stone, terrazzo, and decorative concrete.
3. Stone wall cladding and facades.
4. Paving stones and garden architectural elements.
5. Stone joints requiring moisture protection.
6. Fireplaces and interior stone décor.
7. Restoration and protection of aged stone surfaces.

Technical Specifications & Typical Values

Binder Type	Acrylic
Colour	Available in clear state and in 28 shades upon request .
Diluent	Water
Density at 22°C (ISO 2811)	1.05 Kg/L
Solids %w/w	~ 18 % *
VOC (2004/42/EC)	90 g/L – (A/i/SB) One-pack performance coatings - VOC compliant
Dry film thickness (2 coats) (ASTM D6132-13(2017))	12 µm

*depending on the tinting base

**depending on surface absorption, tinting base & application method

TECHNICAL DATA SHEET

HYDRO CURE

General purpose water based wood impregnant for preservation.

Technical Specifications & Typical Values

Method	Paint brush, roller or spray gun
Coverage per coat	8-10 sqm/L**
Recoatibility	4-6 hours
Shelf life	12-24 months
Touch Dry Time at 22°C	20-40 min
Dry Through Time at 22°C	4-6 hours
Ambient air temperature	min. +10°C / max. +40°C
Relative air humidity	55-60 % max.
Curing time	Note: Times are approximate and will be affected by changing ambient and substrate conditions, particularly temperature and relative humidity.

*Depending on the tinting base

**Depending on surface absorption, tinting base & application method

***Drying times are temperature, humidity, and film thickness dependent

TECHNICAL DATA SHEET

HYDRO CURE

General purpose water based wood impregnant for preservation.

HYDROCURE preparation:

Substrate quality & preparation:

1. The substrate must be cured, solid, clean, dry and free of all contaminants such as dust, dirt, oil, grease, surface treatments, etc.

HYDROCURE preparation and dilution:

In general use dilute with water by 10%

In the case of spray gun application, dilute with water by 10%

Important application remarks:

1. Untreated substrate defects could lead to reflective coating defects and reduced performance.
2. Tool cleaning right after use with soap and water, always following the local HSE rules.

Packaging:

Metal can of:

0.75-L

3-L

9-L

Storage:

Shelf life: 12-24 months from the date of production, in original unopened packaging in a cool and dry condition between +5°C and +35°C. Protect from direct sunlight, heat, temperature extremes, and moisture. Failure to comply with the recommended storage conditions may result in premature deterioration of the product packaging and which may cause inconsistent workability, finish and cure times of the material.

Health, Safety & Environment:

Read the product label carefully before use. The Technical Data Sheet should be read in conjunction with the Safety Data Sheet.

TECHNICAL DATA SHEET

HYDRO CURE

General purpose water based wood impregnant for preservation.

Paint System

Contact Akteon Paints for case-by-case recommendations at: contact@akteonpaints.com or visit www.akteonpaints.com

Disclaimer: The information contained in this publication is based on our scientific knowledge, laboratory studies and long-term experience. Therefore, the information provided must be considered indicative and subject to constant review in relation to the circumstances and each practical application. This information is for use by technically skilled persons at their own discretion and risk. The user alone has the responsibility to ensure that existing laws and legislation are observed when using the products.